



## Crowcon T4X Gas Detector O2, H2S, CO GDS8008

*Versatile and easy to use, the T4x comes with long-life O2 and MPS™ sensor technologies for enhanced general protection.*

The T4x is a portable multi gas monitor providing enhanced personal protection whenever you need. Available with added industry leading sensor technologies (MPS™ and long-life O2) to improve worker safety, remove the risk of device poisoning, and cost you less over time.

T4x is Crowcon's Zone 0 approved personal protection solution for detecting the four most common gas hazards: carbon monoxide, hydrogen sulphide, flammable gases and oxygen depletion, offering you compliance and low cost of ownership in a one simple-to-use solution.

The T4x has three sensor technology options for you to select according to your needs: Dual Toxic sensor for CO and H2S, Long-Life Oxygen (LLO2), and the MPS™ sensor, which has zero risk of device poisoning and can accurately identify over 15 different flammable gases in one device.

The large single button and intuitive menu system allows T4x to be operated wearing gloves with minimal training, and it is durable by design and includes an integrated rubber boot as standard, with all the durability you can expect from the T4 range. Plus, its 35+ hour battery life (double the battery life of our original T4) allows multiple or longer shifts to be worked between recharging, allowing for uninterrupted working in the most demanding environments.

- 130 hours of data logging; Up to 3500 events
- Size: 135 x 80 x 35mm (5.3 x 3.1 x 1.4in)
- Weight: 282g (9.9oz)
- Drop tested 4m onto concrete
- Rechargeable Li-ion - 18 hour typical runtime
- 5.5 hour recharge
- Audible Vibrating Visible
- Audible >95dB
- Integrated
- Bright red & blue LED's

### Product Variants & Options

GAS SENSOR	CONFIGURATIONS		
	2 Gas	3 Gas	4 Gas
Oxygen (O <sub>2</sub> )	■	■	■
Oxygen (O <sub>2</sub> ) Long-Life		■	■
Flammable MPS™		■	■
Flammable Pellistor	■	■	■
Hydrogen sulphide (H <sub>2</sub> S)		■	■
Carbon monoxide (CO)	■	■	■
Carbon monoxide (CO) - H2 immune		■	■

### Gases & Ranges

GAS	RANGE	RESOLUTION
Oxygen (O <sub>2</sub> )	0-30% vol.	0.1% vol.
Oxygen (O <sub>2</sub> ) Long-Life	0-25% vol	0.1% vol
Flammable	0-100% LEL	1% LEL
Hydrogen Sulphide (H <sub>2</sub> S)	0-100ppm	1ppm
Carbon Monoxide (CO)	0-1000ppm	1ppm

Code	Code
<b>GDH8008</b>	<b>GDS8008</b>
<b>1 Week Hire</b> <small>(price each per week)</small>	<b>Guide Purchase Price</b>
<b>£35.00</b> <small>ex VAT</small>	<b>£745.00</b> <small>ex VAT</small>